



**LOCATE WELL CORRECTLY**

NO GAS SALES CONNECTION.

|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |

LOCATE WELL CORRECTLY



U.S. DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company Name \_\_\_\_\_ Address \_\_\_\_\_

Owner or Trust \_\_\_\_\_ Field \_\_\_\_\_ State \_\_\_\_\_

Well No. \_\_\_\_\_ Section \_\_\_\_\_ Township \_\_\_\_\_ Range \_\_\_\_\_

Location \_\_\_\_\_ of \_\_\_\_\_ line and \_\_\_\_\_

Log Released - 8 PM - 12/19/59

The information on this page is for the use of the well owner and is not to be used for any other purpose.

Log points of 2 3/4" casing, set at 3705'.

oil, press. dropped to 1700' and was shut down and to set in 1-hour.

press. 3000', ave. int. rate 53.9 bbls/min. Overlaid with 200 bbls.

formation with 2400', max. casing 1.3100', int. press. 2600', final

30 000' 20 40' and, through above perforations, down 52" casing, broke

through sand and oil. Perforations with 50,000 test gals. of oil sealed and

oil. Bullets per foot.

12-19-59 - Lane-wells Perforated 52" casing from (3678-3724') Chacra Zone, with 2-type

B-R Temperature Survey, found top of cement outside 52" cas. - 1300'-1150'

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.

12-19-59 - Set 52" 15-56' casing - 3678' 1/2" Baker shoe, cemented by Halliburton,

with 400 bag cement, set at 1500', Plug down at 5:30 AM.