\$00-16 7258-259

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R359.4.
Indian Agency Daloe, New Mexico
Jicarilla Apacko

Allottes Cont. 1749-Treet 1246

Lease No. J. Apache "7"

SUNDRY NOTICES AND REPORTS ON WELLS

	SUBSEQUENT REI	ORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO DRILL	3 11		1 1
NOTICE OF INTENTION TO CHANGE		ORT OF SHOOTING OR ACIDIZING	i I
NOTICE OF INTENTION TO TEST WAT		PORT OF ALTERING CASING	· 1 1
OTICE OF INTENTION TO REDRILL		PORT OF REDRILLING OR REPAIR.	
OTICE OF INTENTION TO SHOOT O		PORT OF ABANDONMENT	
IOTICE OF INTENTION TO PULL OR	State and the state of the stat	Report for Perfore	ating &
NOTICE OF INTENTION TO ABANDON	[II Chi	Frechuring	X
(INDICA	TE ABOVE BY CHECK MARK NATURE OF REPORT, N	OTICE, OR OTHER DATA)	
	4	February 21	, 19 63
Vell No. 10 is lo	cated 1190° ft. from N line and	960' ft. from line	of sec. 16,
i/Mi-Sec-16,		MAPM (Meridian)	DEGEIVE
(14 Sec. and Sec. No.)	(Twp.) (Range)	Mari	
sin Dekota	(County or Subdivision)	(State or Territo	OCY)
(Field)	• •		FFR 3 1963
		UT.	
ne elevation of the derric	k floor above sea level is ft.		
ne elevation of the derric	k floor above sea level is 67141 ft.		IL S. CECLOGICAL SURVEY
tate names of and expected depths 2-20-63 - 7428 TD1	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important proportions and all other important proportions. The control of the	us of proposed casings; indicate my sed work) Tool at 3911', (U Liburton Tested 32"	FARMINGTON, NEW MEXICO udding jobs, coment- pper Stage) and Cag. W/4500# Press
tate names of and expected depths 2-20-63 - 7428 TD; drilled cement out o 1/2 Hr. Held OK. Per (7284'-95') W/1-Shot Halliburton Sand-Wat water, Max. Press. A Swabbed well 5 Hr. e to 750%, at end of 3 est. 50 bbls. fractu Well Completed 5:00	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out B.V. f 32" easing to 7316'. Half forated by Lane-Wells from per Ft. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 Bi and started flowing 8 5:00 Pi -Hour test gas vol. 4,257 Mi are water and turned to spray PM, 2/20/63.	reof proposed casings; indicate mind work) Tool at 3911', (United Tested 3g'', 7103'-30')(7240'-4) Corations W/44,000# Relations W/44,000# Relations W/54,000# Relatio	FARMINGTON, NEW MEXICO undding jobs, coment- pper Stage) and Cag. W/4500/ Press. 5')(7250'-56') and Sand & 66,000 Gala- ted 11:30 AM, 2/20/6' Press. from Zero Distillate, made
intenames of and expected depths 1-20-63 - 7428' TD; irilled coment out out out out out out out out out ou	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out D.V. 1 32" easing to 7316'. Hall forated by Lane-Wells from per Pt. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 Bi and started flowing 8 5:00 Pi Heur test gas vol. 4,257 Bi are water and turned to spray PM, 2/20/63. erk must receive approval in writing by the Geolo	reof proposed casings; indicate mind work) Tool at 3911', (United Tested 3g'', 7103'-30')(7240'-4) Corations W/44,000# Relations W/44,000# Relations W/54,000# Relatio	FARMINGTON, NEW MEXICO undding jobs, coment- pper Stage) and Cag. W/4500/ Press. 5')(7250'-56') and Sand & 66,000 Gala- ted 11:30 AM, 2/20/6' Press. from Zero Distillate, made
ate names of and expected depths -20-63 - 7426' TD: rilled cement out o /2 Hr. Held CK. Per /284'-95') W/1-Shet alliburten Sand-Wat alliburten Sand-Wat ater, Max. Press. 4 bebbed well 5 Hr. a co 7500, at end of 3 est. 50 bbls. fractu est. 50 bbls. fractu	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out D.V. 1 32" easing to 7316'. Hall forated by Lane-Wells from per Pt. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 Bi and started flowing 8 5:00 Pi Heur test gas vol. 4,257 Bi are water and turned to spray PM, 2/20/63. erk must receive approval in writing by the Geolo	rical Survey before of Fig. 2.5. Tool at 3911', (U. iburten Tested 32'', 7103'-30')(7240'-4. Corations W/44,000# Residual Survey before of Fig. 2.5. Corations Signature of Signature o	FARMINGTON, NEW MEXICO undding jobs, coment- pper Stage) and Cag. W/4500f Press. 5')(7250'-56') and Sand & 66,000 Gala- ted 11:30 AM, 2/20/6; Press. from Zero Distillate, made
tate names of and expected depths 1-20-63 - 7428' TD: irilled cement out of 1/2 Hr. Held OK. Per 1/284'-95') W/1-Shet Isliburton Sand-Nat sater, Nax. Press. A brabbed well 5 Hr. a to 750%, at end of 3 set. 50 bbls. fractu iell Completed 5:00 I understand that this plan of well company Amerada Peta	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out D.V. 1 32" easing to 7316'. Hall forated by Lane-Wells from per Pt. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 Bi and started flowing 8 5:00 Pi Heur test gas vol. 4,257 Bi are water and turned to spray PM, 2/20/63. erk must receive approval in writing by the Geolo	re of proposed casings; indicate my hid work) Tool at 3911', (United 32'') Tool at 391', (United 32'') Tool at 391	Gag. W/L500# Press. 5')(7290'-56') and Sand & 66,000 Gals. ted 11:30 AM, 2/20/6; Press. from Zero Distillate, made
tate names of and expected depths 2-20-63 - 7428' TD: drilled cement out of 1/2 Hr. Held OK. Per (7284'-95') W/1-Shet Halliburton Sand-Nat water, Max. Press. A Sumbbed well 5 Hr. a to 750%, at end of 3 est. 50 bbls. fractu Well Completed 5:00 I understand that this plan of we Company Amerada Peta	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out D.V. 1 32" easing to 7316'. Hall forated by Lane-Wells from per Pt. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 B and started flowing 8 5:00 P Heur test gas vol. 4,257 B are water and turned to spray PM, 2/20/63. erk must receive approval in writing by the Geolo release Corporation turnego, Colorado	coordinate of proposed casings; indicate mad work) Tool at 3911', (United 32'') Tool at 391'' Tool at 3	FARMINGTON, NEW MEXICO undding jobs, coment- pper Stage) and Cag. W/4500f Press. 5')(7250'-56') and Sand & 66,000 Gala- ted 11:30 AM, 2/20/6; Press. from Zero Distillate, made
tate names of and expected depths 2-20-63 - 7428! TD: drilled cement out of 1/2 Hr. Held CK. Per (7284!-95!) W/1-Shet Halliburten Sand-Nat water, Max. Press. 4 Sumbbed well 5 Hr. a to 750%, at end of 3 est. 50 bbls. fractu Well Completed 5:00 I understand that this plan of we Company America Petr Address Box 1469, I	DETAILS OF WORK to objective sands; show sizes, weights, and length ing points, and all other important propo 7316' BOD: Drilled out B.V. f 32" easing to 7316'. Hall forated by Lane-Wells from per Ft. er Fractured thru above per 5006, Avg. Inj. Rate 22.5 B and started flowing 8 5:00 P Heur test gas vol. 4,257 M are water and turned to spray PM, 2/20/63. erk must receive approval in writing by the Geolo release Corporation hurango, Colorado	corations W/4,000/ liburten Tested 32" 7103'-30')(7240'-4 Corations W/4,000/ lis/Min. Job complete 2/20/43, Casing Ty, W/Show of clear Corations Corac Cora	FARMINGTON, NEW MEXICO and ding jobs, coment- pper Stage) and Gag. W/4500/ Press. 5')(7250'-56') and Sand & 66,000 Galacted 11:30 AM, 2/20/6) Press. from Zero Distillate, made

•