



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SF 078714  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF <del>SAND-ENCLOSING</del> .....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY  
RECEIVED  
SEP 12 1951

September 11 1951

Well No. 1-66v't. is located 790 ft. from [N] line and 790 ft. from [E] line of sec. 36

NE 1/4 Sec. 34 24N 6W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6828 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Production String Details:

4 1/2" J-55 New seamless casing cemented at 6522'  
Top 2 joints 11.6'  
next 145 jts. 9.5'  
bottom 57 jts. 11.6', open guide shoe with float collar at 6492'.  
Cemented 204 joints of 4 1/2" at 6522' with 300 sacks of 50/50 Poz-mix  
followed by 50 sacks of neat. Perforated 4 1/2" casing with 6. 3-1/8"  
jts per foot in interval 6384-6392' (Second Dakota).

Treated perforations with sand-water Free using 30,000# of sand and  
29,000 gals. of "slish" water. Break-down pressure 3800 psig. Treating  
pressure 2000 to 2400 psig. Average injection rate 35.4 bbls./min.  
Instant shut-in pressure 1150 psig., vacuum after two hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Lenn-Mintico  
Mr. Clinton White  
Address P.O. Box 351  
Durango, Colorado.

By John E. Mitchell  
Title Agent.