


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 070667  
Unit Sepp



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 23, 19 57

Well No. 1-B is located 330 ft. from S line and 1650 ft. from E line of sec. 21  
SE Section 21 24N 8W N.M.P.M.  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat San Juan New Mexico  
 (Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 6768 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was plugged and abandoned in the following manner:

1. Set cement plug from 4186 to 4086 with 40 sks. cement.
2. Set cement plug from 3138 to 3088 with 20 sks. cement.
3. Set cement plug from 2250 to 2150 with 40 sks. cement.
4. Set cement plug from 1850 to 1750 with 40 sks. cement.
5. Set cement plug from 1300 to 1200 with 129 sks. cement.
6. Set cement plug from 90 to surface with 40 sks. cement.
7. Set 4' x 4" pipe as marker.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997  
Farmington, New Mexico

By [Signature]  
 Title Petroleum Engineer