

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The summary on this page is for the condition of the well at above date.

Commenced drilling 4-29, 1957 Finished drilling 5-8, 1957

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from _____ to _____ No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
10-3/4	32.75	P.F.	S.W.	161'	Howco				surface

MUDDING AND CEMENTING RECORD

[illegible]

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
See Well History						

TOOLS USED

Rotary tools were used from 0 feet to 4180 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

P & A 5-10, 19-57 Put to producing _____, 19_____

The production for the first 24 hours was ----- barrels of fluid of which -----% was oil; -----% emulsion; -----% water; and -----% sediment. Gravity, °Bé. -----

If gas well, cu. ft. per 24 hours ----- 5,341 ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

_____, Driller

_____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	1044	1044	Tan to gry cr-grn ss interbedded w/gry sh.
1044	1257	213	Ojo Alamo ss. White cr-grn s.
1257	1578	321	Kirtland form. Gry sh interbedded w/tight gry fine-grn ss.
1578	1774	196	Fruitland form. Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.
1774	1846	72	Pictured Cliffs form. Gry, fine-grn, tight, varicolored soft ss.
1846	2192	346	Lewis formation. Gry to white dense sh w/silty to shaly ss breaks.
2192	3090	898	Mesa Verde form. Gry, fine-grn, dense sil ss. carb sh & coal.
3090	4132	1042	Allison-Gibson formation. Gry, fine-grn s, carb sh & coal.
4132	4180	48	Point Lookout form. Gry, fine-grn very fine sil ss w/frequent sh breaks.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NEW BAD SID TO GO OUT

7-952299-43M 10/99

1. Set #1 pipe as marker.

2. Set cement plug from 90 to surface w/ 40 sks.

3. Set cement plug from 1300 to 1750 w/ 40 sks.

4. Set cement plug from 1650 to 1750 w/ 40 sks.

5. Set cement plug from 2250 to 2450 w/ 40 sks.

6. Set cement plug from 3138 to 3088 w/ 20 sks.

7. Set cement plug from 4100 to 4000 w/ 40 sks.

This well was plugged and abandoned in the following manner:

DATE 5-10-57

Sec: 4110-4133

Recovery 401

4101-4129

4129-4180

251

251

RECEIVED
ON COM. COM.
DIST. 3

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

[illegible]