


UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



8-29-57
Ran 166 J
In to set

8-22-57
Cleaned out to 5340'. Perforated 5300-5310' and 5264-78'
with 4 holes per foot.
8-24-57
Open 12 hours after dumping 200 gallons MCA. Slit shot
of oil and gas. Hand-oil treated with 27,000 gallons
oil and 50,000 sand.
The information given here is a complete and correct record of the well and all work done thereon
as far as can be determined from all available records.
Initial breakdown pressure 2200#. Initial
pressure 25,000 gallons
dropped 55 rubber balls and pressure increased to 2200#.
Pressure 1100#. Average injection rate 4.5 barrels per
Company
8-28-57
Total recovery 815 barrels load oil. Gas gauge 100 MCF/day. es
LOG OF OIL OR GAS WELL
Run 166 joints 220' of 2 7/8" OD and casing. Shut well
in to set separator.

8-21-57 Pressured up on 5-1/2 casing to 1000#. No pressure decrease in one hour. OIL ON GAS SANDS OR ZONES

8-20-57 Moved in cable tools.

8-11-57 TD 5364 NKB. Set 5-1/2" casing at 5363' with 150 sacks cement.

Spadded: Set 8-5/8" casing at 194' with 125 sacks cement. Pressured up on casing to 500#. No pressure decrease in 30 minutes.

Continued on next page

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of reworking, repairs, and changes made in the casing, state fully, and if any casing was "sidetracked," or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or boring of shots.

HISTORY OF OIL OR GAS WELL

16-48094-2 U. S. GOVERNMENT PRINTING OFFICE

[illegible]