Form	9-881 a
(Feb	. 1951)

	X	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land (Office .	, A	anta Fe	
Lease !	الله مه	O	78241	L
**	2.	H.	Hessie	

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-O	<u> </u>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CAS	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE I	BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
E. H. Heggie	Farmington, New Mexico May 27 , 1959
Well No is located 19	ft. from $\binom{N}{S}$ line and 1980 ft. from $\binom{E}{W}$ line of sec. 2
	wp.) (Range) (Meridian)
	(County or Subdivision) (State or Territory)
The elevation of the derrick floor al	bove sea level is 6745 ft.
	DETAILS OF WORK
State names of and expected depths to objective ing	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement points, and all other important proposed work)
W. M. Manual at Mark 1 Way 2 and	
easing was set at 203' with After waiting on cement, or	1 160 sacks of esment containing 2% calcium chloride using and water shut off were tested 400 pounds pre- with no drop in pressure. Reduced hole to 7-7/8" a
easing was set at 203' with After waiting on cement, co thirty minutes, which held	1 160 sacks of essent containing 2% calcium chloride using and water shut off were tested 400 pounds pres with no drop in pressure. Reduced hole to 7-7/8" a
easing was set at 203' with After waiting on cement, or thirty minutes, which held resumed drilling operations	160 sacks of ement containing 2% calcium chloride ising and water shut off were tested 400 pounds project in the containing 2% calcium chloride ising and water shut off were tested 400 pounds project in the containing 2% calcium chloride is a state of the containing 2% calcium chlo
easing was set at 203' with After waiting on cement, on thirty minutes, which held resumed drilling operations I understand that this plan of work must received.	nive approval in writing by the Geological Survey before operations may be commenced.
easing was set at 203' with After waiting on cement, or thirty minutes, which held resumed drilling operations	160 sacks of ement containing 2% calcium chloride sing and water shut off were tested 400 pounds provided no drop in pressure. Reduced hole to 7-7/8" and the no drop in pressure. Reduced hole to 7-7/8" and the same state of the
easing was set at 203' with After waiting on coment, on thirty minutes, which held resumed drilling operations I understand that this plan of work must recommonly Pan American Patro	sing and water shut off were tested 400 pounds provide asing and water shut off were tested 400 pounds provide no drop in pressure. Reduced hole to 7-7/8" sive approval in writing by the Gelogical Survey by three operations may be commenced. ORIGINAL SIGNED BY G. L. Hamilton

GPO 862040