


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office **Santa Fe**  
Lease No. **078302-4**  
Unit \_\_\_\_\_

Section 7

RECEIVED

NOV 5 1959

## SUNDRY NOTICES AND REPORTS ON WELLS

U. S. GEOLOGICAL SURVEY	
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 2, 1959

Federal 7-7

Well No. **5** is located **660** ft. from **(N)** line and **1930** ft. from **(E)** line of sec. **7**  
**NW 1/4, NE 1/4 Sec. 7** **24N** **9W** **RMPM**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Bisti-Lower-Gallup** **San Juan County** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6825** ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The well was cleaned out to 5470' and a bridge plug was set at 5440 and the interval 5418-5434 was perforated with 4 jet shots per foot. These perfs were fraced with 15,000 gal. crude and 30,000 lbs. sand at 2300 psi and 35 BPM. The bridge plug was pulled and the well was placed on production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Standard Oil Company of Texas**Address **P.O. Box 1581****Farmington, New Mexico**

By

Title **Field Foreman**

