## UNITED STATES SUBMET IN TRIPLICATE\* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

	Form approved. Budget Bureau No. 42-R1424
١.	LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY SF - 078202-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS tDo not use this term for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME WELL X WELL OTHER East Bisti Unit NAME OF OPERATOR 8. FARM OR LEASE NAME Skelly Oil Company 3. ADDRESS OF OPERATOR 9. WELL NO. 1860 Lincoln Street, Denver, Colorado 80203 108 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT At surface Bisti Lower Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 660' FNL & 660' FWL Section 7-24N-9W Section 7-24N-9W 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 12. COUNTY OR PARISH | 13. STATE 6856' GR 6869' KB San Juan New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF : TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING X SHOOT OR ACIDIZE ARANDON\* SHOOTING OR ACIDIZING ABANDONMENT\* REPAIR WELL CHANGE PLANS (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \* This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows: First Plug - 100' plug across the Gallup zone perfs. 5430-5479' Second Plug - 50' inside 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland coal section across the Pictured Cliffs sand Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand) 10 sacks of cement in top of surface casing with dry hole marker AL SURVEY 18. I hereby certify that the foregoing is true and correct District Operations Supt. June 8, 1971 TITLE DATE (This space for Federal or State office use) APPROVED BY DATÈ TITLE CONDITIONS OF APPROVAL, IF ANY: