

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form Approved
Budget Bureau No. 42 R1424
5. LEASE OR LOCATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME East Bisti Unit	
2. NAME OF OPERATOR Skelly Oil Company		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203		9. WELL NO. 93	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2115' FSL & 2080' FWL Section 4-24N-10W		10. FIELD AND COOR. OF WILDCAT Bisti Lower Gallup	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6918' KB	
11. DEPTH, T. R. M., OR BLK. AND SURVEY OR AREA Section 3 4-24N-10W		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:


First Plug - (5366 - 5466) 100' plug across the Gallup Zone Perfs. 5391-5441'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1660 - 1810) 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (980 - 1080) 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker



18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Bista

TITLE

Lead Clerk

DATE

August 23, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side