

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_  
Lease No. 078623  
Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 23, 1957


Well No. 2 Scott is located 660 ft. from N line and 660 ft. from E line of sec. 3  
NW 1/4 3 24 N. 10 W. N.M.P.M.  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Bisti San Juan New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded April 5, 1957, with 177 feet 9 5/8 set by Halliburton with cement circulated to top. 5 1/2 14# set April 14, 1957  
 Total Depth 5443 feet by Halliburton with 225 sacks of cement 1300 feet fill up behind pipe. By Temperature bomb test.  
 Perforated April 21, 1957 by Lane-Wells Company with their E. Gun. 4 bullets per foot from 5354 to 5368  
 5384 to 5392



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Rex R. Moore, Jr.  
 Address 2904 Liberty Bank Bldg.  
Oklahoma City  
Oklahoma

By Rex R. Moore  
 Title Partner

