

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE
OTHER REVISIONS TO THE
REVERSE SIDE

Form Approved
Bureau of Reclamation No. 40-11624
5. LEASE DESIGNATION AND SERIAL NO.
NM-087657

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.
See APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME Escrito Gallup	
2. NAME OF OPERATOR BCO, Inc.		8. FARM OR LEASE NAME Escrito Gallup Unit	
3. ADDRESS OF OPERATOR 135 Grant, Santa Fe, New Mexico 87501		9. WELL NO. 3 (Smith #2)	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 855' FNL 410' FEL Sec 13 T24N R8W NMPM		10. FIELD AND FORM. OR WILDCAT Escrito Gallup	
14. PERMIT NO.		11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA 13-24N-8W NMPM	
15. ELEVATIONS (Show whether Dr., Rt., Cr., etc.) GR 7089 DF 7098		12. COUNTY OR PARISH 13. STATE San Juan, NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETION	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☒	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)	☐		

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)

July 27, 1987 Dropped 5 bbls diesel down tubing and 5 bbls diesel down casing to kill well.

July 31, 1987 Tagged bottom at 5946'. Tripped out of hole with 2-3/8" tubing (5924' strapped pipe). Tripped in and out of hole with 2-3/8" tubing and casing scraper.

August 3, 1987 Tripped in and out of hole with 2-7/8" tubing and collar locator. Picked up straddle packers. Tripped in hole with 2-7/8" tubing, Baker Straddle Packer, 1 joint of 2-3/8" tubing above and 2 joints of 2-3/8" tubing between packers. Set straddle packer at 5777'-5846'. Filled annulus with 28 bbls crude oil and pressure tested backside to 600 PSI for 15 minutes.

August 4, 1987 Treated 33,400 gallons of water with 84 gallons of TRI-S, 70 gallons of 3N, 5950 lbs of KCL, 35 gallons of LP55 scale check, 700 lbs of WG-11, 50 lbs of HYG-3, 100 lbs of K-34 and 5 lbs GBW-3. Sand water foam fracked 5926'-5934' with 104,600 gallons of 70 quality foam, 122,000 lbs 20-40 sand, and 1,711,600 standard cubic feet of nitrogen. Average treating pressure 4800 PSI at 20 foam bbls per minute. ISIP 2650, 5 min. 2060, 10 min. 1990, 15 min. 1960. Shut in well three hours before flowing back.

(Continued)

18. I hereby certify that the foregoing is true and correct

SIGNED Elizabeth B. Keeshan

TITLE Vice President

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY:

TITLE _____

BY _____

NMOCG

*See Instructions on Reverse Side

RECEIVED
AUG 13 1987
OIL CON. DIST. 3
ACCEPTED FOR RECORD
DATE 8/10/87
AUG 11 1987
FARMINGTON RESOURCE AREA