

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM MAIL ROOM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BCO, INC.

3. Address and Telephone No.

135 GRANT, SANTA FE, NM 87501 (505) 983-1228

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

855' FNL & 410' FEL, NMPM
NE/4 OF THE NE/4 (A)
S13-T24N-R8W

5. Lease Designation and Serial No.

NM-087657

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

ESCRITO GALLUP

8. Well Name and No.

ESCRITO GALLUP U. 3

9. API Well No.

3004513017

10. Field and Pool, or Exploratory Area

ESCRITO GALLUP

11. County or Parish, State

SAN JUAN, NM, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

CERTIFIED RETURN RECEIPT REQUESTED: P626 361 850

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

OIL CON.
DIST. 3

ATTACHMENTS: PLUG AND ABANDONMENT REPORT AND JOB LOG

14. I hereby certify that the foregoing is true and correct

Signed

SENIOR FIELD ENGINEER

Date 06/17/94

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date

JUN 29 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

1000

RECEIVED
BLM 6/27/94
JUN 27 PM 3:49
PLUG AND ABANDONMENT
Escrito Gallup Unit Number 3
Formerly Smith Number 2
855' FNL & 410' FEL, GL=7098'
SECTION 13, TOWNSHIP 24N, RANGE 8W

PLUG AND ABANDONMENT REPORT

June 15, 1994

Mr. Joe Ruybalid with the BLM was on location.

Plug Number 1 from 5951' to 5658', cemented with 45 sacks of Class "B" cement with 2 percent calcium chloride (100 percent excess), TOH to 4000', reversed out, WOC 3.5 hours, TIH and tagged cement at 5482', laid down 60 jts.

Plug Number 2 from 4020' to 3820', cemented with 31 sacks of Class "B" cement with 2 percent calcium chloride (100 percent excess), laid down 53 jts.

Plug Number 3 from 2335' to 1986'. cemented with 34 sacks of Class "B" cement with 2 percent calcium chloride, TOH laying down to 1870', circulated hole clean, TOH.

June 16, 1994

Mr. Joe Ruybalid with the BLM was on location.

TIH with Schlumberger wire line and tagged cement at 1938', perforated 4 holes at 1850', 50' Below the base of the Ojo Alamo.

Plug Number 4 from 1800' to 1554'. TIH with CR and set at 1800', a rate could not be established, the pressure increased to 1200 psig and held, Joe Ruybalid with the BLM approved cementing on top of the cement retainer. , stung out of retainer and spotted 19 sacks of class "B" cement on top of retainer, laid down the remaining pipe.

TIH with Schlumberger and perforated 4 holes at 254'.

Plug Number 5 from 254' to surface. Cemented down the 4 1/2" casing with 96 sx of class "B" cement, there were good returns out the braden head and cement was circulated to surface.

ND BOP, cut off well head below ground level, filled casing with cement and installed dry hole marker.

The final abandonment notice will be submitted after the surface restoration has been completed.



CEMENTERS, INC.

P. O. BOX 302 • FARMINGTON, NEW MEXICO 87499 • (505) 632-3683

DATE 6-14th 15-94

CUSTOMER: BCO

WELL # Escrito Gallup #3

CEMENT USED: _____

DISPLACEMENT BARRELS: _____

CEMENT CIRCULATED: _____

DISPLACEMENT RATE: _____

CEMENT RATE: _____

DISPLACEMENT PRESSURE: _____

PRESSURE: _____

DISPLACEMENT TIME: _____

CEMENT TIME: _____

PLUG BUMP TIMES & PRESSURE: _____

OTHER: _____

① Spotted 45 sx 2% CaCl₂ @ 5951 to 5369

② Spotted 31 sx @ 4020 to 3620

③ Spotted 34 sx @ 2335 to 1938

④ Spotted 19 sx @ 1800 to 1554

⑤ 7 1/2 sx @ 254 to Surf