


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allettee 0562577
Lease No. 14 20 603 1265



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

January 30, 1961

19

Well No. 1-5 is located 660 ft. from N line and 660 ft. from E line of sec. 5

NE 5 24N 10W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Bisti San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6881 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud date October 19, 1960.

179' of 7" 23# 8R used Surface casing. Circulated 50 sacks cement.

30' of 10 3/4" Conductor casing. Circulated 15 sacks cement.

4269' of 15.5# 8R Spang extreme upset casing set as intermediate casing. This was not cemented.

5426' of 2 7/8" 6.5# 8R N-80 used production string. This was cemented with 25 sacks and a fill up to 4900'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company H.F. Sears

Address 424 Petroleum Building

Amarillo, Texas

By Joe C. Stealy

Title Office Manager

