



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. N.M. 37892
Unit 438

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 Vander ^{alice} is located 660 ft. from (N) line and 660 ft. from (E) line of sec. 13
SW (Sec. and Sec. No.) 33 (Twp.) 24N (Range) 12W (Meridian)
Wilcox (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6395 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

- We propose to:
1. Squeeze open perms. 1448-1456' & bring to 1450' or above.
 2. Shoot or cut pipe at free point & pull remaining casing
 3. Set cement plug at top of cut off pipe stab. Will have 50' cement inside pipe & 50' cement above stab.
 4. Mud up to 1650' Cement plug 1650'-1550'.
 5. Mud up to 850' Cement plug 850' to 950'.
 6. Cement plug 50' from bottom of 8-5/8" surface casing.
 7. Set surface marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SOUTHERN UNION GAS COMPANYAddress P. O. Box 415Farmington, New MexicoBy Vernon J. LoweTitle Drilling Superintendent