

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-9577

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NAVAJO

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NAVAJO "X"

9. WELL NO.

NO. 1

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T24N, R20W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ DRY HOLE

2. NAME OF OPERATOR

Kerr-McGee Corporation

3. ADDRESS OF OPERATOR

215 Petroleum Center Bldg. - Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1190° F&L & 1020° F&L; Sec. 20, T24N, R20W.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

8898'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting; any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set the following cement plugs by balanced plug method using drill pipe.

Plug No. 1	250 axs	3560'-4101'(T.D.)
Plug No. 2	50 axs	2828'-2928'
Plug No. 3	50 axs	1338'-1438'
Plug No. 4	50 axs	1140'-1240'

Drilling mud is in the hole between the plugs. A 10 ax plug was placed at the surface and a 4-1/2" O.D. x 4' high dry hole marker was placed on top of the 9-5/8" casing and a steel cap welded between the casing and the marker. Work was complete on 11-22-67. Casing left in the well is 9-5/8" O.D., 32.30', N-40, ST&C casing (surface) set at 1190' and cemented to surface. No casing was pulled. Notice will be given when pit has been filled and location ready for inspection. This work will be done as soon as the pit dries.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Supt.

DATE

11-23-67

(This space for Federal or State office use)

APPROVED BY


TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

2-1000C
2-1000S
1-Tribe
1-JIF
1-W&F
1-RF

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.