

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NOO-C-14-20-3586

6. If Indian, Allottee or Tribe Name

NAVAJO

7. If Unit or CA, Agreement Designation

8. Well Name and No.

DRY CREEK

9. API Well No.

#1

10. Field and Pool, or Exploratory Area

BISTI LOWER GALLUP

11. Country or Parish, State

SAN JUAN, NM

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

COLEMAN OIL & GAS INC

3. Address and Telephone No.

P. O. DRAWER 3337, FARMINGTON, NM 87499

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL-1180' FEL SEC. 5, T24N, R10W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☒ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if work is discontinuously drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

DATES: JULY 29, 30, 31 - 1991

1. SET CEMENT RETAINER AT 5021'
2. ROLL THE HOLE WITH 9# 54 VIS MUD
3. SPOT 25 SX. OF CEMENT FROM 5021" TO 4800' ON TOP OF CEMENT RETAINER
4. SPOT 25 SX. OF CEMENT FROM 2129' TO 1908' & DISPLACE W/6 BBLS OF WATER
5. SPOT 51 SX. OF CEMENT FROM 1620' TO 1170' & DISPLACE W/4 BBLS OF WATER
6. SPOT 51 SX. OF CEMENT FROM 826' TO 376' SHUT DOWN AND TAGGED CEMENT @ 370'
7. PERFORATE CASING AT 55' FILLED CASING AND CIRCULATED CEMENT TO SURFACE
8. CUT OFF BRADEN HEAD AND ERRECTED DRY HOLE MARKER

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title AGENT

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

APPROVED

Date 9/9/91

Date