

HALLIBURTON SERVICES
JOB SUMMARY

DIVISION
HALLIBURTON LOCATION

BILLED ON
TICKET NO.

WELL DATA

FIELD SEC. TWP. RNO. COUNTY STATE
FORMATION NAME TYPE
FORMATION THICKNESS FROM TO
INITIAL PROD: OIL BPD. WATER BPD. GAS MCFD
PRESENT PROD: OIL BPD. WATER BPD. GAS MCFD
COMPLETION DATE MUD TYPE MUD WT.
PACKER TYPE SET AT
BOTTOM HOLE TEMP. PRESSURE
MISC. DATA

	NEW USED	SIZE	FROM	TO	WEIGHT	MAXIMUM PSI ALLOWABLE
CASING	N	4 1/2	0	6000	11.6	1500
LINER						
TUBING						
OPEN HOLE		7 1/8				
PERFORATIONS						SHOTS/FT.
PERFORATIONS						SHOTS/FT.
PERFORATIONS						SHOTS/FT.

JOB DATA

TOOLS AND ACCESSORIES

TYPE AND SIZE	QTY.	MAKE
FLOAT COLLAR		
FLOAT SHOE		
GUIDE SHOE		
CENTRALIZERS		
BOTTOM PLUG		
TOP PLUG		
HEAD P.C.H	1	BAKER
PACKER 4 1/2		
OTHER BAKER TOOL D.V.	1	BAKER

DATE 5-12-75 TIME 1630
DATE 5-13-75 TIME 0100
DATE 5-13-75 TIME 0330
DATE 5-13-75 TIME 0935

PERSONNEL AND SERVICE UNITS

NAME	UNIT NO. & TYPE	LOCATION
Fury	7799	
DAVIS	7133	

DEPARTMENT CEMENT
DESCRIPTION OF JOB CEMENT 2 STAGE 4 1/2 Prod casing
JOB DONE THRU: TUBING ☐ CASING ☒ ANNULUS ☐ TBG./ANN. ☐
CUSTOMER REPRESENTATIVE X Harry X
HALLIBURTON OPERATOR
COPIES REQUESTED

CEMENT DATA

STAGE	NUMBER OF SACKS	TYPE	API CLASS	BRAND	BULK SACKED	ADDITIVES	YIELD CU.FT./SK.	MIXED LBS./GAL.
1	340	Howco Light		B			1.97	12.5
1	235	50/50 Poz		B			1.26	14.1
2	490	Howco Light		B		10# GILSONITE P.S	2.12	12.1

PRESSURES IN PSI

SUMMARY

VOLUMES

CIRCULATING DISPLACEMENT
BREAKDOWN MAXIMUM
AVERAGE FRACTURE GRADIENT
SHUT-IN: INSTANT 5-MIN. 15-MIN.
HYDRAULIC HORSEPOWER
ORDERED AVAILABLE USED
AVERAGE RATES IN BPM
CREATING DISPL. OVERALL
CEMENT LEFT IN PIPE
FEET 41 REASON float
CUSTOMER

PREFLUSH: BBL-GAL. 20 TYPE WATER
LOAD & BKDN: BBL-GAL. PAD: BBL-GAL.
TREATMENT: BBL-GAL. DISPL: BBL-GAL.
CEMENT SLURRY: BBL-GAL.
TOTAL VOLUME: BBL-GAL.

REMARKS
1 STAGE Displ. 40 WATER 52.5 Mud
2 STAGE Displ. 50 BBL WATER
1 STAGE CWT Slurry 171 BBL
2 STAGE " " 185 BBL