Farm 9-331 Dec. 1973

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Form Approved. Budget Bureau No. 42-R1424
5. LEASE	
	OTTEE OR TRIBE NAME
7. UNIT AGREEME	NT NAME
8. FARM OR LEASI	
Gee, I	
#2 10. FIELD OR WILD	CAT NAME
Wildcat 11. SEC., T., R., M., AREA Sec 3	OR BLK. AND SURVEY OR
12. COUNTY OR PA	RISH 13. STATE
San Juan 14. API NO.	NM_
.5. elevations (s 6588' GR	SHOW DF, KDB, AND WID)
(NOTE: Report results change on Fo	of multiple completion or zone rm 9-330.)
ill pertinent details, ctionally drilled, give o this work.)*	and give pertinent dates, e subsurface locations and
	MILLION
	29 1979
	MAY 29 1979 OIL CON. CON. OIL DIST. 3
	VOIL DIST. 3

SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🗔	Gee, I
well well other	9. WELL NO.
Z. NAME OF OPERATOR	#2
Dugan Production Corp.	10. FIELD OR WILDCAT NAME
3 ADDDESS OF ODEDATOD	Wildcat
Box 234, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec 3 T24N R9W
below.)	36C 3 124N K9W
AT SURFACE: 1160' FSL - 950' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL;	San Juan NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6588' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	t wood an
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Description
PULL OR ALTER CASING 🗍	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON* XX [] (other)	
(Other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent. Plan to plug and abandon well as follows:	irectionally drilled give subsurface locations and
1. Spot cement plug from 1670- 1560'	
2. Spot cement plug from 1100 - 900'	
3. Spot surface plug from surface to 100'	
4. Cut off csg below ground level	MAY 29 1979
<ol><li>Erect dry hole marker and clean location.</li></ol>	MAY 29 131 OIL CON. COM. DIST. 3
Subsurface Safety Valve: Manu. and Type	Set @F
18. I hereby certify that the foregoing is true and correct	
SIGNED THOMAS A. Dugan TITLE President	
(This space for Federal or State office	ce use)
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE

\*See Instructions on Reverse Side