in 3160-5 june 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND DEPORTS ON WELLS

PORM	LAPPR	OVED
Budger Bur	ceu No.	1004-0135
Expires:	March	31, 1993

J. Lease Designation and Serial No.

14-20-0603-1409

6.	u	Indian,	Allottee	or	Tribe	Name
1.	- 1	^				

Use "APPLICATION FOR PERMIT—" for such proposals	6. If Indian, Allottoe or Tribe Name	
SUBMIT IN TRIPLICATE	1, 11 Units or CA, Agreement Designation	
1. Type of Well Oil X Gas Well Other P & A 2. Name of Operator	Well Name and No. Sears Roebuck 2	
3. Address and Telephone No.	9. API Well No. 30-045-23202	
P.O. Box 420, Farmington, NM 87499 (505) 325-1821 4. Location of Well (Footage, Soc., T., R., M., or Survey Description)	10. Field and Pool, or Exploratory Area Undes. Fruitland	
1650' FNL - 330' FEL Sec. 5, T24N, R10W, NMPM	II. County or Parish, State San Juan, NM	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT	r, or other data	
TYPE OF SUBMISSION TYPE OF ACTION		
Notice of Intel Abandonment Recompletion Plugging Back Casing Repair DIST. 3 Distrible Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed or complete or details and give pertinent dates, including estimated date of starting and proposed or complete or details and give pertinent dates, including estimated date of starting and proposed or complete or details and give pertinent dates, including estimated date of starting and proposed or complete or details and give pertinent dates, including estimated date of starting and proposed or complete or details and give pertinent dates.	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

nd measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged as follows:

- 1. Used tubing to spot 18 cu. ft. Class B cement plug with 3% CaCl₂ from 1750' to 1550'.
- 2. Wait 2% hrs. and tag plug.
- 3. Load hole with 9 lb./gal. mud.
- 4. Perforate casing at 1,000'.
- 5. Spot 68 cu. ft. Class B cement plug from 1,000' to 780'.
- 6. Perforate casing 50' below surface casing at 265'.
- 7. Pump 90 cu. ft. Class B cement down casing and circulate to surface.
- 8. Set dry hole marker and cut off rig anchors.

Operations Complete 7-24-91.

Approved as to placethy of the well be Liebally ander hour is religious will surface restanction to completed.

Signed John Alexander Title Operations Manager Date 7-30-91 (This space for Federal or State office use) Approved by Title	Conditions of approval, if any:		Deka
Signed John Alexander Title Operations Manager Date 7-30-91	Approved by	Title	AUG 02 1991
	John Alexander	L Tide Operations Manager	Date 7-30-91