

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS. ROOM

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

COLEMAN OIL & GAS, INC.

3. ADDRESS OF OPERATOR

P. O. DRAWER 3337, FARMINGTON, NEW MEXICO 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

330 FNL AND 990FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

6827GR

5. LEASE DESIGNATION AND SERIAL NO.

NOO-C-14-20-3585

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NAVAJO

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DRY CREEK

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

BISTI LOWER GALLUP

11. SEC., T., R., M., OR BLM. AND  
SURVEY OR AREA

SEC. 5, T24N, R10W

12. COUNTY OR PARISH 13. STATE

SAN JUAN

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)

SUBJECT WELL WAS PLUGGED AS FOLLOWS:

8-17-89 DRILLED EXISTING CEMENT TO DEPTH OF 3211' HARD CEMENT OK'D FOR BOTTOM. ROLLED HOLE  
WITH 9# MUD, PERFORATE AT 3100', 2300', 1650', 900'; EXISTING PERFS. OPEN AT 261' &  
50'. RAN IN THE HOLE WITH RETAINER PREMATURELY SET AT 2201'. INCREASED CEMENT  
VOLUME ESTABLISHED INJECTION RATE PUMPED 102 SX OF CEMENT AT 800# DISPLACED CEMENT  
TO TOP OF RETAINER. RAN IN THE HOLE WITH RETAINER SET AT 1300' PUMPED 180 SX OF  
CEMENT DISPLACED TO TOP OF RETAINER. RAN IN THE HOLE WITH RETAINER SET AT 714'  
ESTABLISH INJECTION RATE PUMP 100 SX OF CEMENT. DISPLACE TO TOP OF RETAINER. LAY  
DOWN TUBING ESTABLISH INJECTION RATE DOWN CASING AND FILL BACK SIDE THRU BRADEN HEAD  
PUMP CEMENT THRU 50' PERFS. UP 8 5/8" CASING AND OUT BRADEN HEAD CLOSE BRADEN HEAD  
VALVE SQUEEZE THE REST OF THE 50 SX INTO EXISTING PERFERATIONS.  
8-18-89 CUT OFF WELL HEAD AND INSTALL DRY HOLE MARKER.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED

*George E. Coleman*

TITLE

PRESIDENT

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE 8-28-89

SEP 01 1989

Ken Townsend  
AREA MANAGER  
FARMINGTON RESOURCE AREA

\*See Instructions on Reverse Side