Form 9-331 Dec. 1973

APPROVED BY CONDITIONS OF Form Approved.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form 3-221	Budget Bureau No. 42-R1424
UNITED STATES  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	5. LEASE NN 4958 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME
1. oil gas XXX other  2. NAME OF OPERATOR	April Surprise 9. WELL NO. #2
3. ADDRESS OF OPERATOR P 0 Box 208, Farmington, NM 87401	10. FIELD OR WILDCAT NAME  Basin Dakota  11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  AT SURFACE: 1850' FSL - 800' FWL  AT TOP PROD. INTERVAL:  AT TOTAL DEPTH:	AREA Sec 30 T24N R9W  12. COUNTY OR PARISH 13. STATE San Juan NM  14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6975' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE (NOTE: Report results of multiple completion REPAIR WELL change on Form 9-330.) PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Plan to move in rig, pull 2-3/8" O.D., 4.7# tubing and packer, frac Dakota formation 6122-32' with 30,000 gal gel water, 42,000# 20-40 sand, clean out after frac, run string 11 0.D., 2.4#, V-55, 10R, EUE tubing and put well back on production. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Petroleum Engineer DATE for Federal or State office use)

> FON JAMES F. SIMS DISTRICT ENGINEER

See Instructions on Reverse Side