

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Dome Petroleum Corp.

3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 114, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2280' FSL, 2150' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) Spud & Set Surface Casing

5. LEASE

NM 12374

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dome Federal 35-24-9

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat/Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T24N, R9W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6910' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/4" hole at 3:30 a.m., 9/20/80. Drilled to 245'. Ran 5 jts. (227') 8 5/8", 24#, K55, ST&C Casing. Casing landed at 241' K.B. Cemented with 200 sx. Class "B" Cement with 2% CaCl. Plug down at 12:30 p.m., 9/30/80. Circulated Cement.

RECEIVED

OCT 2 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE Drlg. & Prod. Foreman DATE Oct. 1, 1980

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

OCT 08 1980

*See Instructions on Reverse Side

BY BW FARMINGTON DISTRICT

NMOCC

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐
well well other Dry Hole

2. NAME OF OPERATOR
Dome Petroleum Corp.

3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 114, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2280' FSL, 2150' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF:

RECEIVED

OCT 16 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE

NM 12374

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dome Federal 35-24-9

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat/Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T24N, R9W

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6910' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to plug and abandon as follows:

Plug No.	Interval	Feet	Sacks Cement
1	5135-4985	150	50
2	4115-3965	150	50
3	1675-1525	150	50
4	1050-800	250	75
5	285-135	150	50
6	30-0	30	15

Clean location, fence pits and install dry hole marker. Verbal approval received from Erol Becher at 1:15 p.m. 10/11/80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLLINGSWORTH TITLE Drlg. & Prod. Foreman DATE Oct. 15, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

B. W. W. W.
for

ch 3

*See Instructions on Reverse Side

NMOCC