Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	5. LEASE NM 12233 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas other	SOUTH BLANCO FEDERAL 25	
well well other	9. WELL NO.	
2. NAME OF OPERATOR	4	
MESA_PETROLEUM_CO.	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	LYBROOK GALLUP EXT	
1660 Lincoln, Suite 2800, Denver CQ 80264	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 25-T24N-R8W	
AT SURFACE: 910' FNL & 660' FWL	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL:	SAN JUAN NEW MEXICO	
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
DEGLISOT FOR ARROCKAL TO CURRENT REPORT OF	6895' GL (UNGRADED)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	11500	
TEST WATER SHUT-OFF FRACTURE TREAT	A CONTRACTOR OF THE PARTY OF TH	
SHOOT OR ACIDIZE	COFI'FILM	
REPAIR WELL	(NOTE: Report results of Built personal time) zone	
PULL OR ALTER CASING	change on Ffrm 9-330.)	
MULTIPLE COMPLETE	FEB 2 7 1981	
ABANDON*	OIL CON. COM.	
(other) Spud, cement and test BOP	Jan COM.	
AT DECORRES PROPOSED OF COMPLETED OPERATION TO	DIST. 3	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d		

17 measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well spudded @ 3:30 PM 2/18/81. A 12-1/4" hole was drilled to 263'. Ran 6 joints 8-5/8" 24#/foot new STC K-55 casing. Set casing @ 248' KB. Cemented w/200 sxs Class "B" 2% CaCl. Good circulation throughout. Circulated 14 bbls slurry to the surface. Plug down @ 10:15 PM 2/18/81. Tested BOP to 1,000 psi for 30 minutes and held - OK.

Subsurface Safety Valve: Manu. and Type	Set @	Ft.
Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct  SIGNED / LAGE / LAGE / DIV. Prod. Super. DATE	2/20/81	
(This space for Federal or State office use)		
APPROVED BY CCERTIFIER FURNHECORD TITLE DATE		

FEB 26 1981

**NMOCC**