

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☒ well other ☐
2. NAME OF OPERATOR
COLEMAN OIL & GAS, INC.
3. ADDRESS OF OPERATOR c/o W. M. Callaway
101-2 Petroleum Plaza Bldg., Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
800' FNL, 890' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☒
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
FEB 25 1981
U. S. GEOLOGICAL SURVEY

(NOTE: Report required for multiple completion or zone change in well.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All measurements on 14' K.B.

On 1-27-1981 ran 224' of 8 5/8" 24# surface casing cemented with 125 sacks of Class B, waited 8 hours, tested for 20 minutes to 1000#. Test o.k. Cement was circulated to surface.

On 1-31-1981 ran 5348.51' of 4 1/2" 10.50 casing. Cemented with 200 sacks, bumped plug under 1500# pressure, released, float held. Circulated 2 hours through D.V. tool @ 4243' then cemented with 350 sacks. Circulated good on both stages. Estimated cement top @ 150'.

Subsurface Safety Valve: Manu. and Type D.V. Tool by Baker, Set @ 4243 Ft.
Float by Dowell

18. I, W. M. Callaway, certify that the foregoing is true and correct

By: W. M. Callaway TITLE Engineer DATE Feb. 24, 1981

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MAR 3 1981
FARMINGTON DISTRICT
BY EJW

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.