

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☒ other

2. NAME OF OPERATOR

COLEMAN OIL &amp; GAS, INC.

3. ADDRESS OF OPERATOR c/o W. M. Gallaway

101-2 Petroleum Plaza Bldg., Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 830' FNL, 1650' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☒FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

5. LEASE

N00-C-14-20-3593

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ed White

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Wood

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Bisti Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T24N, R10W

12. COUNTY OR PARISH 13. STATE

San Juan

N. M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6836' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL  
SURVEY  
FARMINGTON, N.M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directional, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

All measurements on 14' K.B.

On 1-21-1981 ran 217' of 8 5/8" 24# surface casing cemented with 125 sacks of Class B, waited 8 hours, tested for 20 minutes to 1000#. Test o.k. Cement circulated to surface.

On 1-27-1981 ran 5374.64' of 4 1/2" 10.50# casing. Cemented first stage with 200 sacks, bumped plug under 1500# of pressure, released. Float held. Circulated 2 hours through D.V. tool @ 4255' then cemented with 350 sacks. Circulated good on both stages. Estimated cement top @ 150'.

Subsurface Safety Valve: Manu. and Type D.V. Tool by Baker.

Set @ 4255 Ft.

Float Equip. by Dowell

18. I hereby certify that the foregoing is true and correct

COLEMAN OIL &amp; GAS, INC.

SIGNED

By: W. M. Gallaway

TITLE Engineer

DATE

Feb. 24, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: