rom 3160-5 November 1983) Formerly 9-331)

14.

16.

UNITED STATES BUBMIT IN TRIPLICATES (Other Instructions on reThe Interior (other instructions on reThe Interior (other instructions on reThe Interior (other instructions) on reThe Interior (ot

Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

	-				
NOO-1	,	200	1 25	^ ^	
N(1(1)	11.	- / 1	1 - 37'	413	

form approved.

BUREAU	NOO-14-20-3593			
SUNDRY NOTION (Do not use this form for proposal Use: "APPLICAT	NAVAJO A //c/ teg			
OIL GAS Y OTESS	59	福福 29 福刊: 07	7. UNIT AGREEMENT NA	MB
NAME OF OPERATOR	S. FARM OR LEASE WANE			
COLEMAN OIL & GAS I	NAVAJO WOOD			
DORESS OF OPERATOR			9. WELL NO.	
P.O. DRAWER 3337	#2			
LOCATION OF WELL (Report location cle	10. FIELD AND POOL, OR WILDCAT			
At surface	BISTI LOWER GALLUP			
83	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA			
			SEC. 9,T24N,	R1OW
PERMIT NO.	15. BLEVATIONS (Show whether DF.	, BT, CB, etc.)	12. COUNTY OR PARISE	18. STATE
	6836 GR		SAN JUAN	N.M.
Check Ap	propriate Box To Indicate N	lature of Notice, Report, or (Other Data	
NOTICE OF INTENT	UBNT EMPORT OF:			
TEST WATER SHUT-OFF	CLL OR ALTER CASING	WATER SHUT-OFF	REPAIRING 1	TELL
FRACTURE TREAT	ULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING C	
SHOOT OR ACIDIZE	BANDON*	BEOOTING OR ACIDIZING	YBTHOOHRE	HT*
REPAIR WELL C	HANGE PLANS	(Other) Report result	of multiple completion	on Well
(Other)			letion Report and Log for	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertiproposed work. If well nent to this work.) *

THE SUBJECT WELL TO REENTER & REPLUG AS FOLLOWS:

+ mud 1529 #/9 al

REMOVE DRY HOLE MARKER, DRILL OUT SURFACE & SURFACE CASING SHOE. TAG 0JO ALAMO PLUG, IF GOOD CEMENT IS IN PLACE, REPLACE ALL CEMENT IN CASING SHOE & ERECT DRY HOLE MARKER. IF NEEDED DRILL OUT ALL CEMENT TO TOP OF CEMENT ON BRIDGE PLUG MAKING SURE OF 300' OF CEMENT ON BRIDGE PLUG.

- ROLL HOLE WITH 9# 50 VIS. MUD.
- PERFORATE CLIFFHOUSE AT 3060' AND CEMENT INSIDE AND OUTSIDE 412" CASING FROM 3060' TO 2960', 35 SKS.
- CHACRA PERF. 2360' SET 35 SK PLUG, INSIDE AND OUT OF $4\frac{1}{2}$ " CASING 2360' TO 2260'. 3.
- PICTURED CLIFFS AND FRUITLAND PERF. 1650' SET 35 SK PLUG, INSIDE AND OUT OF 41/2" CASING 1650' TO 1500' 1270' for 1 plug from 1650-1550 & 4 plug from 1370-1270
- 5. OJO ALAMO PERF. 860' SET 60 SK PLUG INSIDE AND OUT OF $4\frac{1}{2}$ " CASING 860' TO 700'.
- SURFACE PERF. 267' SET 35 SK PLUG INSIDE AND OUTSIDE 41/2" CASING 267' TO 167'. TOP PLUG 50' - O CEMENT INSIDE AND CUT 412" CASING 20 SKS.
- ERECT DRY HOLE MARKER.
- CLEAN LOCATION AND SEED TO SPECIFICATION.

SEE ATTACHED FOR ANDITIONS OF APPROVAL

8. I hereby certify that the foregoing is true and	COFFECT PRESIDENT	MARCH 28, 1989		
(This space for Federal or State office use)		APPROVED KIL		
APPROVED BY	TITLE	AS'AMENDED		
	MADOCO	MAR 3 1 1989		
سريا در.	*See Instructions on Reverse Side	The Kells		