

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
Mesa Petroleum Co.

3. ADDRESS OF OPERATOR  
1660 Lincoln St., #2800, Denver, CO 80264

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL, 970' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Production Casing Report

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

NM 12238

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
South Blanco Federal 25

9. WELL NO.  
#5

10. FIELD OR WILDCAT NAME  
Lybrook Gallup Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 25 - T24N - R8W

12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6862' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Subject well was drilled to TD of 5700' using 7 7/8" bit. Ran 138 joints 4 1/2" 10.5#/ft. new K-55 STC production casing and set at 5659'. Cemented 1st stage with 20 bbls weighted preflush, 350 sxs 50-50 pozmix containing 2% gel 6/10 of 1% fluid loss agent. Cemented 2nd stage with 20 bbls scavenger slurry, 400 sxs 65-35 pozmix containing 6% gel, 6 1/4#/sack gilsonite, 100 sxs 50-50 pozmix containing 2% gel & 6 1/4#/sack gilsonite. Good circulation.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Randy Nordmark TITLE Reg. Coordinator DATE 8/13/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

NMOCC

\*See Instructions on Reverse Side

BY 664