

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil ☒ gas ☐ other

Mesa Petroleum Co.

1660 Lincoln Street, Suite 2800 Denver, CO 80202

AT SURFACE: 330' FSL, 950' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

REQUEST FOR APPROVAL TO:

## TEST WATER SHUT-OFF

## FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

**MULTIPLE COMPLETE**

## CHANGE ZONES

ABANDON\*

(other) ☐ Production Casing Report ☒

SUBSEQUENT REPORT OF:

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-380.)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).\*

Drilled 7 7/8" hole to TD at 5720'. Ran 139 joints 4 1/2" 10.5#/ft. new K-55 STC production casing to 5705'. Cemented 1st stage to 3076', using 350 sxs 50-50 pozmix + 2% gel. Good circulation. Cemented 2nd stage as follows: 20 bbls Scavenger slurry followed by 450 sxs 65-35 pozmix & 6% gel & 6 1/4#/sack gilsonite. Tailed in with 100 sxs 50/50 pozmix & 2% gel & 6 1/4#/sack gilsonite. Circulated cement to surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

**18. I hereby certify that the foregoing is true and correct**

SIGNED Randy Hardsven TITLE Regulatory Coord. DATE July 21, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

**NMOCC**

**\*See Instructions on Reverse Side**

JUL 28 1981

E.