Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

1	FORM APPROVED				
Budge	t Bur	eau No.	1004	-0135	
Ex	pires:	March	31, 8) 93	

	Expues.	March	31, 13	"
Leese	Designati	on and	Scriel	No.

· 7. If Unit or CA, Agreement Designation

N	00-	-C-	14-	20-	-845	52
6.	If L	dian.	Allot	tee or	Tribe	Name

SUNDRY NOTICES AND REPORTS ON WELLS FIRE 13 AND 11: 15

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals—1

Navajo

SUBMI	7. If Unit of CA, Agreement Designation	
1. Type of Well Oil Gas Well Well Other		8. Well Name and No.
2. Name of Operator Banage Greegy Dugan Production Corp.		South Blanco Navajo 25#2 9. API Well No.
P.O. Box 420, Farmington,		30 045 25098 10. Field and Pool, or Exploratory Area
330 FSL & 2000 FEL (SW/4 Student O, Sec. 25, T24N, R8W	Lybrook Gallup 11. County or Parish, State San Juan County, NM	
12. CHECK APPROPRIATE BOX((s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF	ACTION
X Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
Subsequent Report FFR 2	2 1935 Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing Other	Conversion to Injection Dispose Water
13. Describe Proposed or Completed Operations (Clearly state al	្តែ នា	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) te of starting any proposed work. If well is directionally drilled,

It is intended to plug and abandon this well as follows:

- 1.) Set a cast iron bridge plug 50' above the Gallup perforations
 @ 5364'. Cap with 100' of cement covering the top of Gallup
 @ 5318'.
- 2.) Perforate 50' below the Mesa Verde top @ 3447'. Spot 100' cement inside and outside of casing.
- 3.) Spot cement plug from 1983' to 1731' covering top of Pictured Cliffs @ 1933' and Fruitland @ 1781'.
- 4.) Spot 100' plug across Ojo Alamo @ 1275'.

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5.) Spot cement plug from 50' below surface casing @ 241' to surface.

6.) Set dry hole man	ker.	·	
4. I hereby certify that the foregoing is true and correct Signed	Tide	Operations Manager	Date 2/12/96
(This space for Federal or State office use) Approved by	Title		ARPROVED
Conditions of approval, if any:			FEB 20 936