

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTRECEIVED
BLMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

66 SEP - 4 PM 12:32

FARMINGTON, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

BANNON ENERGY
c/o Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 2000' FEL (SW/4 SE/4)
Unit O, Sec. 25, T24N, R8W

5. Lease Designation and Serial No.

NOO-C-14-20-8452

6. If Indian, Alibon or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Blanco Navajo 25#2

9. API Well No.

30 045 25098

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This wellbore was plugged on 8/29/96 as follows:

POH with tubing. Set CIBP @ 5334' and capped with 100' cement. Pull up hole with tubing. Perforated casing at 3447'. TIH to 3448'. Spot 39 sks class "B" with 4% gel. Pull up hole. Displace cement to 3298'. Pull up hole to 1985'. Spot 44 sks class "B" with 4% gel plug inside casing from 1985' to 1225'. Pull up hole to 298'. Fill casing to surface with 25 sks class "B" with 4% gel. TOH.

Cut off wellhead and set dry hole marker on 8/30/96.

Job was witnessed by Kevin Schneider (BLM).

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Manager

Date 9/3/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOCD

APPROVED

SEP 5 1996