

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Mesa Petroleum Co.
3. ADDRESS OF OPERATOR
1660 Lincoln St. #2800, Denver CO 80264
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL, 2295' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

(other) Production Casing Report



5. LEASE
NM 12233
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
South Blanco Federal 26
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Lybrook Gallup Extension
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 26-T24N-R8W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6842' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well was drilled to TD of 5680' on 1/25/82 using a 7-7/8" bit. Ran 134 joints new 4 1/2" 10.5#/foot K-55 STC production casing and set at 5676'. Float collar located at 5637', DV tool at 3071'. Cemented first stage with 450 sacks class "B", tailed in with 150 sacks "self-stress". Circulated 20 barrels to surface. Cemented second stage with 400 sacks 65-35 pozmix, tailed in with 50 sacks class "B". Circulated 25 barrels cement to the surface.

450
150
400
50
50

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED Randy Nordman TITLE Reg. Coordinator DATE 2/1/82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:



ACCEPTED FOR RECORD

FEB 1 1982

*See Instructions on Reverse Side

NMOCC

BY [Signature] FARMINGTON DISTRICT