Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 13612
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well & other	Snuffle-upagus
Wen Const	9. WELL NO.
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.	2 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wildcat Dakota
P O Box 208, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 870' FSL - 840' FWL	Sec 27 T24N R12W
AT SURFACE: 870' FSL - 840' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan NM 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFI NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECLIFET FOR ARRONAL TO. SURGEOUENT REPORT OF	6097' GL & 6109' RKB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	15 -
FRACTURE TREAT	DEGE IND.
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9430) 6 1983
MULTIPLE COMPLETE	OAN 61983
CHANGE ZONES	OIL CON DI
(other) XX Spud & 8-5/8"	Casing OIL CON. DIV.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	e all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and
12-31-82 603' W.O.C. Move In and Rig Up Four Spudded 12½" hole @ 5:00 p.m. 12-30-14 jts. 8-5/8" O.D. 23#, 8RD, ST&C of 599' RKB. Cemented with 350 sacks of slurry - 413 cu.ft.). P.O.B. @ 5:15 circulated approximately 2 Bbls. 3/159', 3/4 degree @ 314', 1/2 degree 1/4 degree @ 603.	-82. Drilled to 603'. Ran casing. T.E. 585.49' set @ class "B" plus 2% CaCl (Total cases and 12-31-82. Cement 4 degree @ 96', 3/4 degree @
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
() (a) \\ (colories	1-3-83
/Jim L. Jacobs	DATE
(This space for Federal or State offi	ce use)
APPROVED BY	MATE - NOUZPIEB TOR TEBORD