| Form 3160-5 (November 198 (Formerly 9-3 | DEPARTMENT OF THE INTERIOR verse alde) | 5. LEASE DESIGNATION AND SERIAL NO. |
|---|--|---|
| | BUREAU OF LAND MANAGEMENT | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| (Do no | SUNDRY NOTICES AND REPORTS ON WELLS to use this form for proposals to drill or to deepen or plus back to a different use the company of the c | el dir |
| OIL WELL | WELL OTHER Dry Hole JUN 10192 | 7. UNIT AGREEMENT NAME |
| 2. NAME OF OR | PERATOR | 8. FARM OR LEASE NAME |
| | Production Corp. | Snuffle-upagus |
| 3. ADDRESS OF | ox 208, Farmington, NM 87499 | 2 |
| 4. LOCATION OF | well (Report location clearly and in accordance with any State sequirements. | |
| See also spo At surface | ace 17 below.) | Undesignated M.V. |
| 870' F | FSL - 840' FWL JUN 0 5 1985 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA |
| 14. PERMIT NO. | BUREAU OF LAND MANAGEN FARMINGTON RESOURCE AF | |
| 11. 128812 80. | 6097' GL: 6109' RKB | San Juan NM |
| 16. | Check Appropriate Box To Indicate Nature of Notice, | |
| | NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
| TEST WATE | ER SHUT-OFF PULL OR ALTER CASING WATER SHUT-O | DEF REPAIRING WELL |
| FRACTURE | | ATMENT ALTERING CASING |
| SHOOT OR | ACIDIZE ABANDON* SHOOTING OR A | ACIDIZING ABANDONMENT® X |
| REPAIR WE | CHANGE PLANS (Other) | Report results of multiple completion on Well |
| (Other) | Completi | on or Recompletion Report and Log form.) |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* | | |
| This well was plugged and abandoned in the following manner: | | |
| 1.) Mixed 21 sacks cement (25 cf). Squeezed 15 cf cement into perfs 2101-2132' and left 10 cf cement in casing from 2132-2020'. Displaced plug with 9.2 # mud. | | |
| 2.) | .) Shot off $4\frac{1}{2}$ " casing at 984'. | |
| 3.) | Spotted cement plug 1034' to 872' - 36 sacks cement (42 cf). Note: tagged plug after setting up at 879'. | |
| 4.) |) Spotted cement plug 650' to surface - 158 sacks cement (186 cf). | |
| 5.) | 5.) Installed dry hole marker. | |
| 6.) Cut off anchors 3' below ground. | | |
| 7.) Filled pits and restored location as per BLM instructions. | | |
| 8.) Placed berms in access road as per BLM instructions. | | |
| 18. I hereby ce | THORK COMPLETED 5=21-85. | APPROVED |
| | VI 2 VI 4 | METALY |

SIGNED

Jim L Jacobs

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

Surface restantion approved

Bend requirements met *See Instructions on Reverse Side

FARMINGTON RESOURCE AREA