

m 3160-5  
vember 1983)  
merly 9-331)

3 BLM 1 File  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**BUREAU OF LAND MANAGEMENT**

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

**RECEIVED**

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR  
DUGAN PRODUCTION CORP.

NOV 26 1985

ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87499

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL - 1980' FWL

PERMIT NO.

16. ELEVATIONS (Show whether DF, RT, CR, etc.)

6640' GL; 6652' RKB

5. LEASE DESIGNATION AND SERIAL NO.

NM 22044

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gold Medal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 33, T24N, R10W, NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

**Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data**

**NOTICE OF INTENTION TO:**

TEST WATER SHUT-OFF


PULL OR ALTER CASING


FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

**SUBSEQUENT REPORT OF:**

WATER SHUT-OFF


FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in and rigged up Four Corners Drilling Company Rig #3.  
Spudded a 12 $\frac{1}{4}$ " hole @ 6:30 PM 11-22-85. Drilled to 215'.  
Ran 7 jts. 8-5/8" OD, 24#, J-55, 8 Rd ST&C casing (T.E. 196')  
set at 209' RKB. Cemented with 135 sx class "B" plus 2% CaCl<sub>2</sub>  
(total cement slurry 159 cf). P.O.B. @ 10:45 PM 11-22-85.  
Circulated  $\frac{1}{2}$  bbl good cement.

Pressure tested BOP & surface casing 600 psi for 30 minutes  
before drilling out - held OK.

**RECEIVED**  
JAN 23 1986

OIL CON. DIV.  
DIST. 3

ACCEPTED FOR RECORD  
DATE 11/25/85

I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OPERATOR

\*See Instructions on Reverse Side