

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. V-1509

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator DUGAN PRODUCTION CORP.	8. Farm or Lease Name Mary Lou
Address of Operator P O Box 208, Farmington, NM 87499	9. Well No. 3
Location of Well UNIT LETTER <u>I</u> . 1980 FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>24N</u> RANGE <u>10W</u> NMPM.	10. Field and Pool, or Wildcat South Bisti-Gallup
15. Elevation (Show whether DF, RT, GR, etc.) 6608' GL; 6620' KB	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
REPAIR OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <u>Spud, Surface Casing & Pressure Test</u> <input checked="" type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in & rigged up Four Corners Drilling Company rig #8.
Spudded a 12 $\frac{1}{4}$ " hole @ 4:15 PM on 3-28-87. Drilled to 215'.
Ran 7 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 196') set
@ 208' RKB. Cemented with 180 sacks class "B" plus 2% CaCl₂
(212 cf). P.O.B. @ 8:15 PM 3-28-87. Cement circulated to surface.

Pressure tested BOP & surface casing 600 psi for 30 minutes before
drilling out - held OK.

MAR 31 1987

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

<u>Jim L. Jacobs</u>	TITLE <u>Geologist</u>	DATE <u>3-30-87</u>
Original Signed by <u>FRANK T. CHAVEZ</u>	SUPERVISOR DISTRICT <u>3</u>	DATE <u>MAR 31 1987</u>
CONDITIONS OF APPROVAL, IF ANY:		