

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved/
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

87 OCT 13 AM 9:21

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR Coleman Oil and Gas, Inc.	3. ADDRESS OF OPERATOR P.O. Drawer 3337, Farmington, New Mexico 87499	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1740' FSL and 1980' FWL	5. LEASE DESIGNATION AND SERIAL NO. NM-54366	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Anderson	9. WELL NO. 1	10. FIELD AND POOL, OR WILDCAT Lybrook Gallup	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, T24N, R8W NMPM	12. COUNTY OR PARISH San Juan	13. STATE N.M.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6,825' GR											

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
(Other) Spud & Casing Report

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/11/87 Spudded well. Drilled 12-1/4" hole to 224'. Ran 8-5/8, 24#, K55 casing and cemented at 214' with 177 cu. ft. cl B ccm w/2% CaCl2. Cement to the surface.

9/12/87 Prtstd. casing to 700 psi before drilling out.

9/18/87 Drilled 7-7/8" hole to a total depth of 5615'.

9/19/87 Ran 4-1/2", 10.5# and 11.6#, K55 casing and cemented at 5615' in 2 stages. First stage 505 cu. ft. of 65:35 pozzolan cement with 6% gel and 1/4# cello flake per sack followed by 118 cu. ft. of cl. B cement. Second stage 803 cu. ft. of 65:35 pozzolan cement with 6% gel and 3.5# H.-Seal per sack. Stage tool @ 2994'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE 10/8/87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 16 1987

*See Instructions on Reverse Side