

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 5686

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER - TITE HOLE - CONFIDENTIAL	7. Unit Agreement Name N/A
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Squash Blossom State
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER N FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 36 TOWNSHIP 24N RANGE 10W NMPM.	10. Field and Pool, or Wildcat S. Bisti-Gallup Oil Est.
15. Elevation (Show whether DF, RT, GR, etc.) 6928' GR	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Perforate, Treat & Sand Frac <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-20-88. Drilled DV tool at 3801'.
10-21-88. Perforated 4992-5022' w/20 .40" holes as follows: 4992-95' w/1 SPF (4 holes); 5005-10' w/1 SPF (6 holes); 5017-22' w/2 SPF (10 holes).
10-22-88. Frac'd (via 4½" casing) w/50000 gals gelled KCL water and 90000# 20/40 sand. Perforated 4544-4850' w/26 .40" holes as follows: 4544, 46, 48, 64, 66, 68' (6 holes); 4601, 06, 07, 26, 28, 46, 48, 53, 70, 71' (10 holes); 4806, 07, 26, 27, 28, 29, 44, 46, 48, 50' (10 holes). Acidized 4544-4850' w/2000 gals 7½% NEFE acid + 45 ball sealers. Frac'd perforations 4544-4850' (via 4½" casing) w/70000 gals gelled KCL water + 120000# 20/40 sand.

TITE HOLE - CONFIDENTIAL!

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>Frank T. Chavez</i>	TITLE Production Supervisor	DATE 10-24-88
-------------------------------	-----------------------------	---------------

APPROVED BY Original Signed by FRANK T. CHAVEZ	TITLE SUPERVISOR DISTRICT #	DATE OCT 24 1988
--	-----------------------------	------------------

CONDITIONS OF APPROVAL, IF ANY: