

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-045-27561
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-1360

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471	8. Well No. 1
3. Address of Operator 105 South 4th St., Artesia, New Mexico 88210	9. Pool name or Wildcat Bisti-Lower Gallup Ext.	
4. Well Location Unit Letter J : 2180 Feet From The South Line and 2145 Feet From The East Line Section 32 Township 24N Range 9W NMPM San Juan County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6846' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Production Csg, Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5171'. Reached TD 2:00 PM 2-7-90. Ran 121 joints 4 1/2" 10.5# J-55 ST&C casing set 5171'. Regular guide shoe set 5171', float collar set 5127'. DV tool set 3552'. Cemented 1st stage w/400 sx 50/50 Poz + 6 1/2#/sx Gilsonite, 1/4#/sx Flocele (yield 1.33, wt 13.2). Tail in w/50 sx C1 B Neat (yield 1.18, wt 15.6). PD 12:45 2-8-90. Circ thru DV tool 2-3/4 hrs. Circ 135 sx cement. 2nd Stage: 685 sx 65/35 Poz w/12% gel, 6 1/2#/sx Gilsonite, 1/4#/sx Flocele, .4% CF-2, (yield 2.26, wt 11.8). Tail in w/50 sx C1 B Neat (yield 1.18, wt 15.6). PD 4:30 PM 2-8-90. Circ 150 sx to surface. WOCU 13 days. Perforated 4782-5057' w/40 .42" holes as follows: 4782, 84, 86, 88, 90, 4800, 02, 04, 06, 08, 10, 4909, 10, 11, 26, 42, 43, 50, 51, 52, 55, 56, 57, 62, 63, 64, 80, 81, 85, 86, 87, 91, 92, 93, 97, 5002, 03, 04, 56, 57. Acidized perfs in three stages w/2500 g. 7 1/2% acid. Frac'd 4782-5057' w/100000 g. gel+145000# 20/40, 30000# 12/20 sd. Perforated 4389-4639' w/43 .42" holes as follows: 4389, 90, 97, 98, 99, 4468, 69, 70, 76, 78, 80, 92, 93, 94, 4514, 15, 16, 17, 51, 52, 61, 62, 63, 64, 71, 73, 77, 78, 83, 84, 94, 95, 96, 97, 4610, 11, 19, 21, 23, 25, 36, 37, 39. Acidize 4389-4639' w/2500 g. 7 1/2% acid. Frac'd 4389-4639' w/100000g. gel+145000# 20/40, 30000# 12/20 sand. NOTE: Drilled DV tool 3552' before perforating.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-1-90
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT III DATE 3-2-90
CONDITIONS OF APPROVAL, IF ANY: