Form 3160-5 (June 1990) DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM 4958 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well X Well Other 2. Name of Operator Dugan Production Corp. 3. Address and Telephone No.		8. Well Name and No. April Surprise #90 9. API Well No. 30 045 29188
P.O. Box 420, Farmington, NM 87499 (505) 325-1821 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area Basin Fruitland Coal
2370' FSL & 930' FWL (NW/4 SW/4) Unit L, Sec. 19, T24N, R9W		11. County or Parish, State San Juan County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR		<u> </u>
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of latent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other TD, casing & cement	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
T.D. 1720' reached on 11-9-94. Circulate hole. Laid down drill pipe. TIH with 39 jts. 4½ 11.6‡ K-55 casing landed at 1719', float collar at 1682'. Circulate 3 hours. Work on pump truck. Pump 10 bbls water. Cement with 100 sx 2½ lodense & tail with 65 sx neat (282 cu.ft.). Displace with 26 bbls water. Plug down at 2230 hrs 11-21-94. Bump plug with 1200 psi - held OK. Circulate trace of cement.		

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side