

BENSON-MONTIN-GREER DRILLING CORP.

GENERAL OFFICE:

2808 FIRST NATIONAL BLDG.
OKLAHOMA CITY 2, OKLAHOMA
PHONE CENTRAL 5-0846

FARMINGTON, NEW MEXICO
PHONE DA 5-8874

#1 BOLACK

CORE DESCRIPTIONS

<u>CORE #5</u>	Cored 3320' to 3380'. Cored 60', recovered 60'.
3320-21'	Hard light grey very very fine micaceous sandstone, thin laminations.
3321-31'	Medium hard light grey silty micaceous sandstone.
3331-40'	Dark grey very fine micaceous shale.
3340-43'	Hard light grey very very fine micaceous sandstone.
3343-44½'	Hard light grey medium fine varicolored sandstone.
3344½-53'	Medium soft light grey medium fine varicolored sandstone.
3353-55½'	Light grey very fine silty micaceous shale.
3355½-63'	Dark grey very fine micaceous shale.
3363-70½'	Dark to light grey very fine hard micaceous shale.
3370½-80'	Hard light grey medium fine micaceous silty sandstone.
 <u>CORE #6</u>	 Cored 3457' to 3517'. Cored 60', recovered 60'.
3457-66½'	Hard light grey very fine silty sandstone.
3466½-70½'	Hard light grey very fine silty sandstone, thin laminations.
3470½-77½'	Hard light grey green very fine silty sandstone.
3477½-84'	Hard dark grey green silty micaceous shale and very very fine green hard silty sandstone.
3484-85½'	Hard light grey green silty sandstone, clay ball inclusions.
3485½-3512'	Hard light grey green silty sandstone.
3512-17'	Soft light grey to varicolor sandstone.