

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Ballard Formation Pictured-Cliffs County Rio Arriba
Initial X Annual _____ Special _____ Date of Test January 18, 1957
Company Western Natural Gas Company Lease Federal-Mordhaus Well No. 6
Unit X Sec. 19 Twp. 25 Rge. 7 Purchaser E.P.N.G.
Casing 5 1/2 Wt. 15 1/2 I.D. 4.95 Set at 2253 Perf. 2134 To 2216
Tubing 1" Wt. 1.70 I.D. 1" Set at 2209 Perf. 2194 To 2208
Gas Pay: From 2130 To 2216 L 2134 xG 0.66 -GL 1408.4 Bar.Press. 12.0
Producing Thru: Casing X Tubing _____ Type Well Single-Gas
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: January 1, 1957 Packer _____ Reservoir Temp. 93° F.

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter)

Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						640.8		640.8		
1.		3/4	446		54	455.0		446.0	54	3 hours
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	14.1605		458	1.0058	0.99244	1.048	6784.6
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 652.8 P_c 426.15

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						209.76	216.38		0.702
2.									
3.									
4.									
5.									

Absolute Potential: 12,069.7 MCF MCFPD; n 0.85

COMPANY Western Natural Gas Company
ADDRESS 823 Midland Tower, Midland, Texas
AGENT and TITLE S. J. Stanley, Engineer
WITNESSED
COMPANY Benson-Mortin-Greer Drlg. Corp.

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressibility factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received 2		
DISTRIBUTION		
TO:	FURNISHED	
Mr. []	/	
Mr. []	/	
Mr. []	/	
Mr. []	/	
Mr. []	/	
Mr. []	/	
File	/	✓