

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
MERIDIAN OIL

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
990'FNL, 990'FWL, Sec.24, T-25-N, R-6-W, NMPM

5. Lease Number  
SF-078879

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
Canyon Largo Unit

8. Well Name & Number  
Canyon Largo U #53

9. API Well No.  
30-039-05950

10. Field and Pool  
Ballard Pictured Cliffs

11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

1-10-95 MIRU. ND WH. NU BOP. TOOH w/83 jts 1 1/4" tbg. SDON.

1-11-95 TIH w/cmt retainer, set @ 2634'. PT tbg to 1000 psi, OK. Established injection w/10 bbl wtr. Plug #1: pump 55 sx Class "B" cmt below cmt retainer and 10 sx Class "B" cmt above cmt retainer. Spotted wtr to 2477'. Pump 20 bbl wtr. Plug #2: pump 29 sx Class "B" cmt @ 2377-2477'. Spotted wtr to 2148'. Plug #3: pump sx Class "B" cmt @ 2048-2148'. PT csg to 500 psi, OK. Perf 2 sqz holes @ 1930'. Unable to pump into sqz holes (verbal approval for change of plans by Wayne Townsend of BLM). TIH to 1960'. Plug #4: pump 33 sx Class "B" cmt @ 1830-1960'. TOOH. Perf 2 sqz holes @ 400'. Plug #5: establish circ down csg and out bradenhead. Pump 80 sx Class "B" cmt down csg and out bradenhead. Circ 1 bbl cmt to surface.

1-12-95 NU BOP. Cut off WH. Top off cmt strings w/6 sx cmt. Install dry hole marker w/10 sx cmt. RD. Well plugged and abandoned 1-12-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 1/13/95

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

APPROVED

JAN 19 1995

DISTRICT MANAGER

NMOCD