

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078631  
Unit Poster "A"  
NW/4 Sec. 8 is  
Designated Drilling  
Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24th, 1956

Well No. 1 is located 790 ft. from [N] line and 1107 ft. from [E] line of sec. 8

NW/4 NW/4 Sec. 8  
(1/4 Sec. and Sec. No.)

25N  
(Twp.)

7W  
(Range)

N.M.P.M.  
(Meridian)

Ballard Ext.  
(Field)

Rio Arriba  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6540 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pictured Cliffs Sand test. Estimated total depth 2500'.

Surface Casing: 90' of 8-5/8" OD 24# J-55 casing cemented to surface.

Production " : Approximately 2500' of 5-1/2" OD 15.5# J-55 casing cemented with 100 sacks.

If commercial production is indicated, the 5-1/2" casing will be perforated and the producing section sandfraced.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company RETRO-ATLAS CORPORATION

Address 7th Floor, Simms Building

Albuquerque, New Mexico

By Tom Bolack  
Title President



