

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **078631**
Unit **Poster "A"**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 20th, 19**56**

Well No. **1** is located **790** ft. from **{N}** line and **1107** ft. from **{W}** line of sec. **8**

NE/4 NE/4 Sec. 8 **25N** **7E** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Ballard Ext. **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6540** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

10-25-56 TD 2421' NMB. Set 53 joints 1712' of 5-1/2" OD 15.5# J-55 casing and 20 joints 640' of 5-1/2" OD 14# J-55 casing at 2360' NMB with 175 sacks cement.

11- 1-56 Pressured up on casing to 1000#. No pressure decrease in one hour.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **PETRO-ATLAS CORPORATION**

Address **1010 North Dustin**

Farmington, New Mexico

By **Tom Bolack**

Title **President**



