| Form 9-881a<br>(Feb. 1951) |  |  |  |  |  |
|----------------------------|--|--|--|--|--|
|                            |  |  |  |  |  |
|                            |  |  |  |  |  |
| •                          |  |  |  |  |  |

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| Land Office | N.M.   |  |
|-------------|--------|--|
|             | 011639 |  |
| Lease No    |        |  |
| Unit        |        |  |
|             | C      |  |
|             | 0      |  |

|  | CAL SURVEY   |
|--|--|
|  | P  |
| SUNDRY NOTICES AND   | D REPORTS ON WELLS Y   |
| HONGE OF INTENTION TO DRILL  | SUBSEQUENT REPORT OF WATER SHUT-OFF  |
| NOTICE OF INTENTION TO DRILL   | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING   |
| NOTICE OF INTENTION TO CHANGE PEARS  | SUBSEQUENT REPORT OF ALTERING CASING.  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL   | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR   |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE  | SUBSEQUENT REPORT OF ABANDONMENT.  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.   | SUPPLEMENTARY WELL HISTORY   |
| NOTICE OF INTENTION TO ABANDON WELL  |  |
|  |  |
| (INDICATE ABOVE BY CHECK MARK NAT  | TURE OF REPORT, NOTICE, OR OTHER DATA)   |
|  | June 12 , 195  |
| Well No. 4 is located 790 ft. from   | Shine and $1850$ ft. from $\{W\}$ line of sec. $5$   |
| SW/4 Sec. 5 & T25N R7W   | NMPM (Meridian)  |
| Largo Picture Cliff Rio Arriba (Field) (County or St   | New Mexico (State or Territory)  |
|  |  |
| The elevation of the derrick floor above sea level   | S OF WORK  |
|  |  |
| (State names of and expected depths to objective sands; snow sizes, ing points, and all other  | weights, and lengths of proposed casings; indicate mudding jobs, ceme<br>er important proposed work) |
| 100 feet 8 5/8" surface casing.  | , circulate cement. Drill 7 7/8'   |
| e to approximately 40' into Lewi   | is Formation. Set 4½" 11 pound   |
| e to approximatery to into item.   | 050 50% nomiles 50%  |
| sing to total depth cemented with  | 250 sacks, 50% regular, 50%  |
| Mix cement. Perforate pay zone   | with 2 shots per foot. Sand oil  |
| JMIR JOHOLIU 2020222 F. J. 20202   | a ar ooo mounds gond. Plush  |
| is mist with the terminal of the contraction of the | and 15 ()() hounds same recom  |
| ic well with to,000 Barrons the  | and 15,000 pounds sand. Flush  |
| th 3,000 gallons oil. Produce the  | hrough 2 3/8" tubing.  |
| th 3,000 gallons oil. Produce the  | hrough 2 3/8" tubing.  |
| th 3,000 gallons oil. Produce the  | hrough 2 3/8" tubing.  |
| th 3,000 gallons oil. Produce the  | and 15,000 pounds samu. Fush hrough 2 3/8" tubing.   |
| th 3,000 gallons oil. Produce the  | hrough 2 3/8" tubing.  |
| I understand that this plan of work must receive approval in w   | nrough 2 3/8" tubing.  |
| I understand that this plan of work must receive approval in w   | hrough 2 3/8" tubing.  |
| I understand that this plan of work must receive approval in w   | hrough 2 3/8" tubing.  |
| I understand that this plan of work must receive approval in w  Company C.J. Warren  525 Solar Road N.W.   | hrough 2 3/8" tubing.  CO/verting by the Geological Survey before operation may be commenced.        |
| I understand that this plan of work must receive approval in w   | hrough 2 3/8" tubing.  CO/verting by the Geological Survey before operation may be commenced.        |
| I understand that this plan of work must receive approval in w  Company C.J. Warren  525 Solar Road N.W.   | hrough 2 3/8" tubing.  |

The second secon

- The second of the second of

The state of the s

Note that the second of the se the state of the s e a tradition of the contract \* Programme to the companies of the comp A Company of the second of the Profession of the contraction of

