

UNITED STATES

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 20 1998

RECEIVED

SEP 24 PM 12:13

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
USE APPLICATION FOR PERMIT—" for such proposals.

OIL CON. DIV.

DIST. 3

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM8F-011639

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Liberman #4

9. API Well No.

30-039-06131

10. Field and Pool, or Exploratory Area

BALLARD PC Field.

11. County or Parish, State

Rio Arriba Co., N.M.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Kimbell Oil Company of Texas

3. Address and Telephone No.

500 THROCKMORTON ST., Suite 3000, Ft. Worth, TX. 76102

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FSL & 1850' FWL Section 5, T25N, R7W

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plug And Abandon well as follows: (1) Circulate hole with water from plug back total depth of 2362' inside 4 1/2" 11.6 #/ft J-55 Casing; (2) Set Cement Retainer AT 2200'; Mix and pump 60 sx Class "B" cement; Squeeze perforations @ 2207'-2238' with 50 sx AND Leave 10 sx. inside 4 1/2" Casing on top OF Retainer; (3) Perforate 3 HSC Squeeze holes at 1650'; Set 4 1/2" cement Retainer AT 1600'; Mix and pump 60 sx Class "B" cement - Squeeze 50 sx. outside Casing with 1000 psi pressure AND leave 10 sx inside Casing to Cover Ojo Alamo Top; (4) with 85 sx. Class "B" cement from 200' to Surface - circ. Good Cement out Breakhead; (5) Cut off Casing 3' Below G.L.; (6) Install Marker.

14. I hereby certify that the foregoing is true and correct

Signed

J. M. Hildner

Title Operations Engineer

Date 7/22/98

(This space for Federal or State office use)

Approved by

/s/ Duane W. Spencer

Title

Date

JUL 30 1998

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NM0007