| Form (April | |
|-------------|--|
| | |

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| Indian Agency |
|------------------------|
| licarilla |
| Allottee Contract #120 |
| Lease No. |

| OTICE OF INTENTION TO DRILL | | SUBSECULENT | REPORT OF WATER SHUT-OFF | X |
|--|---|--|--|----------------|
| OTICE OF INTENTION TO CHANGE F | | | REPORT OF SHOOTING OR ACIDIZING | |
| OTICE OF INTENTION TO TEST WAT | | | REPORT OF ALTERING CASING | |
| OTICE OF INTENTION TO REDRILL | | 1 1 | REPORT OF REDRILLING OR REPAIR | |
| OTICE OF INTENTION TO SHOOT OF | | | REPORT OF ABANDONMENT | |
| OTICE OF INTENTION TO PULL OR | | | ARY WELL HISTORY. | 9.95 |
| IOTICE OF INTENTION TO ABANDON | | JOI P LEMENT | HELL HISTORI | F |
| OTICE OF INTENTION TO ABANDON | WELL | | | A, C |
| (INDICAT | TE ABOVE BY CHECK M | ARK NATURE OF REPORT | , NOTICE, OR OTHER DATA) | |
| | | ******************************* | August 28 | 19 _5 7 |
| ell No. <u>*C* 11=32</u> is loc | cated 1850 ft. | from | d 1650 ft. from $\left\{\begin{matrix} E \\ XX \end{matrix}\right\}$ line of | sec <u>32</u> |
| Sij/4 NR/4 32 (14 Sec. and Sec. No.) | 26N (Twp.) | (Range) | (Meridian) | |
| Wildest (PC) | R: | io Arriba | New Mexico | |
| (Field) | (Cor | unty or Subdivision) | (State or Territory) | |
| | ing points, and | all other important pro | gths of proposed casings; indicate muddi posed work) | |
| Spud 12k" hole at 3 ; OD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate mudd | /8" to |
| Spud 12k" hole at 3 ; DD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; DD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; DD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; OD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; OD J-55 32# 8-RD cas: | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; DD J-55 32# 8-RD cas: Burface w/125 sz reg | ing points, and pm 8-10-57. ing with Bake w/22 CACL. | w sizes, weights, and len all other important pro Prid to 1304 er guide shoe PGS 11:30 pm | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to |
| Spud 12k" hole at 3 ; DD J-55 32# 8-RD cas: surface w/125 sz reg #OC, casing tested O | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15 of 8-5 at 128.87 . Comented | /8" to rs |
| Spud 12k" hole at 3 pm J-55 32# 8-RD cassurface w/125 sx reg 20C, casing tested of | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | /8" to rs |
| Spud 12k" hole at 3 port of work and that this plan of work and the p | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | /8" to rs |
| Spud 12k" hole at 3 pm J-55 32# 8-RD cassurface w/125 sx reg foc, casing tested of the splan of world many | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | /8" to rs |
| Spud 12k" hole at 3 pm J-55 32# 8-RD cas: purface w/125 sx reg #OC, casing tested of | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | /8" to rs |
| Spud 12k" hole at 3 pm J-55 32# 8-RD cas: purface w/125 sx reg #OC, casing tested of | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130 er guide shoe POS 11:30 pra drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | /8" to rs |
| Spud 12k" hole at 3 pm of world at this plan of world at th | ing points, and pm 8-10-57. ing with Bake w/22 CACL. K. Prup to | w sizes, weights, and len all other important pro Prid to 130* er guide shoe POB 11:30 pm drill. | gths of proposed casings; indicate muddiposed work) and set 118.15° of 8-5 at 128.87°. Cemented 3-10-57. After 24 hou | to |