

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office San Juan
Lease No. 1401306
Unit Gardner

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 16, 1960

Well No. 1 is located 1350 ft. from N line and 1000 ft. from E line of sec. 29


23 20 21 2 1401306
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Pinolejo Ext. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 792 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud 11-2-60. Cemented 8 5/8" casing at 102' with 50 sacks. Drilled 7 7/8" hole to 3951'. Ran Schlumberger log. Cemented 4 1/2", 9.5#, J-55 casing at 3946' with 150 sacks. Perforated Pictured Cliffs 3886-63, 3869-77, 3881-85, and 3891-3903 with 2 holes/foot. Perforated Pictured Cliffs down casing with 40,000 gals. water and 40,000 lbs. cement. Breakdown pressure 1500-1950. Injection rate 14" tubing to 3919'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John L. Ryan

Address Box 205

Parlington, New Mexico

By Jack A. Cole
Title Consultant