Form Approved.

Dec. 1973	Budget Bureau No. 42-81424			
UNITED STATES	5. LEASE			
DEPARTMENT OF THE INTERIOR	NM 01806			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME			
1. oil	Gardner			
well Well Other	9. WELL NO.			
2. NAME OF OPERATOR Western Oil & Minerals, Limited	10. FIELD OR WILDCAT NAME Gavilan PC			
3. ADDRESS OF OPERATOR P. O. Drawer 1228, Farmington, N.M.	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17				
	J-29-T26N-R2W			
AT SURFACE: 1850/5 800/E	12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico			
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba   New Mexico			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	- 14. API NO.			
REPORT, OR OTHER DATA	14. API NO.  14. API NO.  1983			
OURSE OUT DEPOS OF	1Er \			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT TEST WATER SHUT-OFF	$\mathcal{E}_{2\alpha}$			
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  SUBSEQUENT REPORT  OFF  OFF  OFF  OFF  OFF  OFF  OFF	OCICION Change on Form 9-330.)			
SHOOT OR ACIDIZE	NEWAY NEW TONE OF THE PROPERTY			
PULL OR ALTER CASING	OGICAL Change on Form 9-330.)			
MULTIPLE COMPLETE	Me.			
CHANGE ZONES U U V FAR ABANDON*				
(other)				
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones perting	directionally drilled, give subsurface locations and			
Dequest to temperary abandon See	attached Conditions for TA			
Request to temporary abandon.				
Well is capable of producing small amotime cannot buck high gathering line p	unts of gas but at present ressure in the area.			
Well is commercial due to stripper sta	tus classification.			

Set @ \_ Subsurface Safety Valve: Manu. and Type \_ 18. I hereby certify that the foregoing is true and correct met/Line Agent January 10, 1983 DATE (This space for Federal or State office use)

\*See Instructions on Reverse Side

DATE

										'
			FIE	LD DY.	TA SHEE	T				,
Туре Те	pe Test: Initial Annual Special 6/12/82							Logge Mo180 Social No.		
Compeny Western Oil and Minerals, Limited								Allottee		
Field Reservoir Location								Unit		
Completion Date Total Depth Plug Back TD Elevation						Form of Lease Nome				
Cag. Sixe	•	Wr.	٠,	Set At	Р	erforation	s: From		To	Well No.
Tbg. Size Wt. d Set At			Perforations: From To				Sec. Twp - Rik Ros - Sur J-29-T26N-R2W			
Txpa Cor	ngletion	( Describe	)					Poc	ker Set At	
Producing			rvoir Temp	. F	Mean Ar	mual Temp	. F	Boro.	Press Pg	Store New Mexico
L		Н	<u> </u>		% CO <sub>2</sub>	7,	N <sub>2</sub>	%	H <sub>2</sub> s	Prover Meter Run Taps
DATE	ELAP.	WELLHEAD	WORKING		ME	TER OR	PROVER			REMARKS
Time of Reading	TIME Hrs.	, The Paig	Ceg. Palg	Tomp.	Pressure Paig	DH.	Temp.	Ori-		lude figuid production data; pe — API Gravity — Amount
11/82					-50			75/	W	
:50A					50		<del> </del>	.250	luli	ned on
:18P					2.2.5			.12		
:33P					2 /			-11		
2:48P			<del> </del>		28			11		
						· · · · · ·				
2:55P			<del> </del>				89	11		
1:00P					29		85	71		
:19P					291/2		87	11		
L:25P					29 3/4			11		
					29 3/4	·				
/12/8; L:45A	-				28		86	.125		
L:50A										
LIJUA									Shu	t in
									Use	d 2" orfice well tes
									17.	06 MCFD
						· 				
							•			
										<u> </u>
										•
			L	!	GE 1 O	F D		}	en fin	·/

In order to place a well in an acceptable condition for temporary abandonment, it is necessary to place either a bridge plug or cement plug no more that 50 feet above the upper most perforations and close the well in at the surface. If a bridge plug is used, it must be capped with cement. The cement cap must be the greater of 35 feet or 5 sacks of cement if placed by dump bailer or, 25 sacks if spotted by tubing. If a cement plug is used it must be the greater of 100 feet or 25 sacks of cement.

Temporary abandonment approved for lyear from date of approval.